


DIMENSIONS (mm)



Cap : E40/45 (IEC 61-1)
 Bulb : soft glass

<u>ELECTRICAL DATA:</u>		<u>NOMINAL VALUE</u>	<u>MIN.</u>	<u>MAX.</u>
Lamp Wattage	(W) :	150		
Lamp Voltage	(V) :	100	85	115
Lamp Current	(A) :	1.8		
Lamp Warm-up current	(A) :		1.8	3

OPERATING CONDITIONS:

Burning Position	:	any		
Ballast Type	:	SHP-150W/220V, 230V, 240V, 250V		
Voltage/Current ratio	:	99		
Calibration Current	(A) :	1.8		
Supply Voltage	(%) :		92	106
Ignitor Pulse	(kVp) :		2.8	5
Compensation Capacitor	(µF) :	20		
Cap Rim Temperature	(°C) :			210
Bulb Temperature	(°C) :			310

LAMP LIFE :

Rated Average Life	(h) :	32000 (50% survival rate)
T 90	(h) :	16000 (90% survival rate)

PHOTOMETRIC DATA :

Initial Luminous Flux	(lm) :	18 000
Luminous Efficacy	(lm/W) :	120
Correlated Colour Temperature	(K) :	2050
Colour Rendering Index	(class) :	4

ATTENTION : Lamps comply with the requirements of IEC publication 60662. Ballasts and ignitors must comply with IEC 60923 and 60927 respectively. Luminaires must be in accordance with IEC 60598-1 and 60598-2-3. Inspection is in accordance with IEC 60410.

Issued by : TIENEN
 Date : 14.03.1990
 Revision date : 31.10.2012

DATA SHEET

Specification No. : 45 27 150/H
 Supersedes : 4527150/G 19.06.2009
 Page 1 of 1