


DIMENSIONS (mm)



Cap : E40/45 (IEC 61-1)
Bulb : soft glass

ELECTRICAL DATA:		NOMINAL VALUE	MIN.	MAX.
Lamp Wattage	(W) :	150		
Lamp Voltage	(V) :	100	85	115
Lamp Current	(A) :	1.8		
Lamp Warm-up current	(A) :		1.8	3

OPERATING CONDITIONS:

Burning Position	:	any		
Ballast Type	:	SHP-150W/220V, 230V, 240V, 250V		
Voltage/Current ratio	:	99		
Calibration Current	(A) :	1.8		
Supply Voltage	(%) :		92	106
Ignitor Pulse	(kVp) :		2.8	5
Compensation Capacitor	(µF) :	20		
Cap Rim Temperature	(°C) :			210
Bulb Temperature	(°C) :			310

LAMP LIFE:

Rated Average Life	(h) :	24000 (50% survival rate)
T 90	(h) :	12000 (90% survival rate)

PHOTOMETRIC DATA :

Initial Luminous Flux	(lm) :	15000
Luminous Efficacy	(lm/W) :	100
Correlated Colour Temperature	(K) :	2000
Colour Rendering Index	(class) :	4

ATTENTION : Lamps comply with the requirements of IEC publication 60662. Ballasts and ignitors must comply with IEC 60923 and 60927 respectively. Luminaires must be in accordance with IEC 60598-1 and 60598-2-3. Inspection is in accordance with IEC 60410.

Issued by : TIENEN
Date : 03.09.2008
Revision date : 29.03.2010

DATA SHEET

Specification No. : 45 - 25 - 150/E
Supersedes : 45-25-150/D 14.09.2009
Page 1 of 1